




Linear LED Fixture Spec Sheet



Our **LYLBR2.3** is an attractive decorative suspended circular light fixture with a 2.3" diameter, available in custom sizes and configurations from **2-8ft**. Easily suspend from any ceiling type using the provided suspension kits. Its circular design gives it a decorative modern finish and a 360 degree light output, making this an attractive option for offices, retails stores, conference rooms, residences, and hotels.


Features


- 12-24VDC Input.
- **Dimmable** (Pair with Dimmable Driver).
- 90+ CRI Standard, 95+ available.
- 624 lumens/ft.
- Suspension Kits Included!
- Waterproof Available Upon Request.
- Made in the USA Quick Ship!
- UL-Listed.

Typical Lumen Table									
Product Size	SO								
4ft	2,496 LM / 24W								
6ft	3,744 LM / 36W								
8ft	4,992 LM / 48W								
*Based on standard sizes with 4000K Color Temperature									

Specifications	*[XX] denotes color temperature
Part#	LVLBR2.3-XX-YY-ZZ
Sizes	4ft, 6ft, 8ft Custom
Input Voltage	12VDC or 24VDC
Light Output	SO: 624 Lumens/ft (White)
Efficiency	104 Lumens/Watt
Color Rendering	>90 CRI, >95 CRI
Environment	Suitable for Dry or Damp Locations
Warranty	5-Year
Lifetime	70,000+Hours
Listings	UL-Listed
Dimming	0-10V Dimmable, Phase/TRIAC
Light Distribution	Down Light








Bluegate Inc. GlowbackLED® 1173 NW 159th Drive Miami Gardens, FL 33169 1-800-679-4902 • info@bluegateinc.com






























*Remote Power Supplies MUST be left accessible, they cannot be installed behind finished ceilings.











All of our LED Panels require a remote power supply and/or controller to operate. Seamlessly integrate our LED Panel systems with any type of home or building automation system. Unless otherwise specified, all LED Panel systems, including power supplies and controllers are shipped to you pre-configured, to facilitate installation. Power-Supplies will come "rigged" with connectors to match the connectors coming off the LED panels. When ordering, simply give us some details about the level of control that you want, and our team will design a turn-key control system fit to meet your needs.













All of our LED Panels require a remote power supply and/or controller to operate. Seamlessly integrate our LED Panel systems with any type of home or building automation system. Unless otherwise specified, all LED Panel systems, including power supplies and controllers are shipped to you pre-configured, to facilitate installating installate installation. Power-Supplies will come "rigged" with connectors to match the connectors coming off the LED panels. When ordering, simply give us some details about the level of control that you want, and our team will design a turn-key control system fit to meet your needs.



Master Produc	t Code Builder
Prefix	LVLB
Profile	R2.3
Finish	
Satin Aluminum	leave blank
Matte Black	N/A
Matte White	N/A
Custom	С
Output	
624 Lumens/ft	SO
000 Lumens/ft	N/A
Size	
2ft	24
4ft	46
6ft	68
8ft	90
Custom	enter in inches
Continous	CR
Custom Shape	CS
Color	
2300K	AW
2700K	IW
3000K	ww
	NW
4000K	
6000K Custom	BW enter CCT value
	RGBW
RGB+6000K	
RGB+2700K	RGBWW CCT
Tunable White	CCI
CRI 90+	90
95+	95
	95
Mount Type Mount to JBOX	A
Remote JBOX	A B
	_
Drop Ceiling	С
High Bay	D
Voltage	
12VDC	leave blank
24VDC	24
Dimming/Control	
0-10V	leave blank
Phase/TRIAC	TRIAC
DMX	DMX
Run Type	
Single	leave blank
C/R Powered End	CRP
C/R Middle	CRM
C/R End Piece	CRE
NA	leave blank
Shapes	
NA .	leave blank
Standard Shape	S/S
Custom Shape	C/S





Non-Dimmable Adaptor	24V 36W	24V36WAPT	
	24V 60W	24V60WAPT	
Non-Dimmable Hardwire	24V 36W	24V36WHOD	
	24V 96W	24V4ALP13	
Phase Dimmable	24V 30W	MUD24V30W	
	24V 60W	MUD24V60W	
	24V 96W	MUD24V96W	
	24V 192W (2 x 96W)	MUD24V192W	
	24V 288W (3 x 96W)	MUD24V288W	
0-10V/Triac Dimmable (All-in-One)	24V 60W	M01024V60W	
	24V 96W	M01024V96W	
	24V 192W (2 x 96W)	M01024V192W	
	24V 288W (3 x 96W)	M01024V288W	
	24V 384W (4 x 96W)	M01024V384W	
Non-Dimmable Hardwire for RF/DI	MX 24V 96W MeanWell	MWHLG100H24A	
	24V 150W* MeanWell	MWHLG150H24A	
RF Receiver and Remotes	RF Receiver (12-24V Input)	BG1009FA	
	Power Repeater (12-24V Input)	BG3002	
DMX Receivers	DMX Receiver (12-24V Input)	BG2108FA-4CH	
	DMX Receiver (12-24V Input) w/ XLR and RJ45 Connectors	BG2108A-M5-5	
All-In-One Built in Power Supply Receiv	RF Receiver (100-277VAC Input) 96W	BG1009FA-96CVF-2	
	DMX Receiver (100-277VAC Input) 96W	BG2108-96CVF-24	
DMX Controllers	Single Zone RGB/RGBW Touch Panel	BG2812B	
	3-Zone RGB/RGBW Touch Panel	BG2812-3(W)	
	Programmable Single Zone Nicolaudie Stick GU2	STICKGU2	
	Programmable Single Zone Nicolaudie Stick CW4	STICKCW4	
	Programmable 10 Zone Nicolaudie Stick DE3	STICKDE3	







Project Name		

Ord	ering Fo	rm											
QTY	LVLBR2.3	Finish	Output	Size	Color	CRI	Mount Type	Voltage	Dimming/Control	Emergency	Run Type	Shapes	Project Fixture Type
	LVLBR2.3	BLK	50	90	ww	90	Α						ST-5
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3											/	
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												
	LVLBR2.3												

Custom Configuration Notes		