



LVLBY33-XX-YY-ZZ


LVLBY33 Spec Sheet




Our LVLBY33 LED Light Fixture is perfect for use in commercial or residential areas. Our LVLBY33 is a 3 inch wide line-voltage recessed linear LED light fixture capable of holding high output strips, making it suitable for a wide variety of linear lighting applications and an excellent solution for lighting garages, warehouses, or industrial lighting. With a slight flange, this fixture can be seamlessly recessed into any surface with at least 3" of depth while hiding any imperfections in the mounting surface. Our LVLBY33 features an integrated driver that allows one to plug the fixture directly into the line-voltage power source of the location. This fixture is available in standard sizes ranging from 24"-96" *custom sizes available upon request* as one continuous run, or in longer runs which can be achieved through linkable or custom configurations.

Features

- 120-277VAC or 347VAC Input
- Standard >80 CRI, CRI>90 available!
- Flange **conceals** any rough cuts in wood and drywall
- 0-10V Dimmable (With Dimmable Driver)
- Ultra Long Lifetime (70,000+ Hours)
- UL-Listed
- 5-Year Warranty





	Quick Specs
Sizes	From 24"-90" (Linkable For Long runs)
Input Voltage	120-277 or 347VAC
Power Output	Power Output Per Size
	SO 2ft: 16W 4ft: 31W 6ft: 47W 8ft: 62W HO 2ft: 28W 4ft: 55W 6ft: 83W 8ft: 104 W
Light Output	Lumen Output Per Size
	SO 2ft :1,368 4ft : 2,736 6ft : 4,104 8ft : 5,472 HO 2ft :2,486 4ft : 4,972 6ft : 7,458 8ft : 9,944
Efficiency (lu/W)	SO: 88 Lumens/Watt HO: 90 Lumens/Watt
Lifetime	50,000+ Hours (L-50)
Lifetime Environment	50,000+ Hours (L-50) Suitable for Dry or Damp Locations













SO: 684 lu/ft **HO:** 1,243 lu/ft

24: 2ft **46:** 4ft **68:** 6ft

WW: 3000K **NW:** 4000K **BW:** 5000K

Mount Type A: Direct-Screw B: Drop-Ceiling Power Entry A: Rear B: End-Cap

> **Glowback**LED® is a registered trademark of Bluegate Inc ©2018 Bluegate Inc. All Rights Reserved Specifications subject to change without notice

