


Linear LED Fixture Spec Sheet



Our **LVLBR4** is a 4" round, pendant (suspend- ed) mounted linear LED fixture. It's beautiful, linear and round design has made it a popular lighting solution for a wide variety of residential, retail, com- mercial, office, and industrial lighting applications.

This linear LED fixture is available in **4ft**, **6ft**, and **8ft** sizes as one single piece. Choose from (2) light output levels: **SO** High Output (847 lumens/ft), or **HO** Ultra High-Output (1,540 lumens/ft). Conveniently select from (3) standard color temperatures best suited to your space: **3000K** (Warm White), **4000K** (Natural White), **5000K** (Bright White).

Integral driver technology allows these fixtures to accept **universal 120-277VAC** input voltage, and are **fully dimmable to 1%** via 0-10V dimming wires. Select a suspension mounting kit suitable to your installation type on the following page.

Features

- Universal **120-277VAC** Input.
- 0-10V **Dimmable**.
- 80+ **CRI** Standard, 90+ available.
- Multiple Light Distribution Options!
- Suspension Kits Included!
- High Quality Look and Build.
- Made in the **USA** Quick Ship!
- **UL-Listed**.

Typical Lumen Table

Product Size	SO	HO
2ft	1,917 LM / 19W	2,825 LM / 25W
4ft	3,673 LM / 36W	5,413 LM / 48W
6ft	5,430 LM / 52W	8,002 LM / 71W
8ft	7,187 LM / 69W	10,591 LM / 93W

*Based on standard sizes with 4000K Color Temperature

Specifications

*[XX] denotes color temperature

Part#	LVLBR4-XX-YY-ZZ
Sizes	4ft, 6ft, 8ft, Custom
Input Voltage	120-277 VAC
Light Output	SO: 959 lumens/ft HO: 1,413 lumens/ft
Efficiency	105 Lumens/Watt, 114 Lumens/Watt
Color Rendering	>80 (CRI over 90 available)
Environment	Dry or Damp Location
Warranty	5-Year
Lifetime	50,000-70,000+ Hours
Listings	UL-Listed
Dimming	0-10V Dimmable, Phase/TRIAC
Light Distribution	Down Light

Available Colors




*Custom Available Upon Request






Finish Options

Standard	Custom
Satin Aluminum	Ruby Red RAL #3003
	Traffic Yellow RAL #1023
	Bright Orange RAL #2009
	Island Skye RAL #6027
	Beige RAL #1001
	Sky Blue RAL #5015

*Extended lead times for custom RAL finishes. Any RAL color can be selected in addition to the one shown

Light Distribution





Standard Shapes			Custom Shapes				
L Configuration	Rectangle/Square Configuration	U Configuration	X Configuration	T Configuration	Hexagon Configuration	Triangle Configuration	Linear Abstract Configuration

*More custom shapes are available upon request

Master Product Code Builder	
Prefix	LVLB
Profile	R4
Finish	
Satin Aluminum	leave blank
Matte Black	N/A
Matte White	N/A
Custom	C
Output	
959 Lumens/ft	SO
1,413 Lumens/ft	HO
Size	
2ft	N/A
4ft	46
6ft	68
8ft	90
Custom	enter in inches
Continuous	CR
Custom Shape	CS
Color	
3000K	WW
4000K	NW
5000K	BW
Custom	enter CCT value
RGB+5000K	N/A
RGB+2700K	N/A
Tunable White	N/A
CRI	
80+	leave blank
90+	90
95+	95
Mount Type	
Mount to JBOX	A
Remote JBOX	B
Drop Ceiling	C
High Bay	D
Voltage	
120-277VAC	leave blank
347VAC	347
Dimming/Control	
0-10V	leave blank
Phase/TRIAC	TRIAC
DMX	DMX
Emergency	
None	leave blank
EM Back Up	EM* 4ft min for EM
Run Type	
Single	leave blank
C/R Powered End	CRP
C/R Middle	CRM
C/R End Piece	CRE
NA	leave blank
Shapes	
NA	leave blank
Standard Shape	S/S
Custom Shape	C/S

