


# Linear LED Fixture Spec Sheet



Our 2" x 4" Linear LED Fixture is a pendant mounted linear up-light/down-light suitable for a wide variety of residential, commercial, retail, office, and hospitality lighting applications.

It is available in **4ft, 6ft, and 8ft** sizes as one single piece. Select "linkable" option for seam-less continuous runs over 8ft. Choose from (3) light dis-tribution types: Direct/Indirect (70% Down, 40% Up); Half and Half (50% Up, 50% Down), and Indirect/Di-rect (30% Down, 70% Up).

Conveniently select from (3) standard col-or temperatures best suited to your space: **3000K** (Warm White), **4000K** (Natural White), **5000K** (Bright White). Integral driver technology allows these fixtures to accept **universal 120-277VAC** input voltage, and are **fully dimmable to 1%** via 0-10V dimming wires. Includes 8ft power and premium stainless steel sus-pension cable.

## Features

- Universal **120-277VAC** Input.
- 0-10V **Dimmable**.
- 80+ **CRI** Standard, 90+ available.
- 423 **lumens/ft** per surface (MAX)
- Suspension Kits Included!
- High Quality Look and Build.
- Made in the **USA** Quick Ship!
- **UL-Listed**.

## Typical Lumen Table

Size	70U/30D	30U/70D	50U/50D	Watts
4ft	4,386U/1,880D	1,880U/4,386D	3,132U/3,132D	62
6ft	6,579U/2,820D	2,820U/6,579D	4,698U/4,698D	94
8ft	8,772U/2,820D	3,760U/8,772D	6,264U/6,264D	125

\*Based on standard sizes with 4000K Color Temperature

### Specifications

\*[XX] denotes color temperature

<b>Part#</b>	LVLBP24-XX-YY-ZZ
<b>Sizes</b>	4ft, 6ft, 8ft, Custom
<b>Input Voltage</b>	120-277 VAC
<b>Light Output</b>	Up/Down: 360-770 Lumens/ft
<b>Efficiency</b>	77 Lumens/Watt
<b>Color Rendering</b>	>80 (CRI over 90 available)
<b>Environment</b>	Dry or Damp Location
<b>Warranty</b>	5-Year
<b>Lifetime</b>	50,000-70,000+ Hours
<b>Listings</b>	UL-Listed
<b>Dimming</b>	0-10V Dimmable, Phase/TRIAC
<b>Light Distribution</b>	Up/Down

### Available Colors






\*Custom Available Upon Request

### Finish Options

Standard	Custom
<ul style="list-style-type: none"> <li>Satin Aluminum</li> <li>Matte Black</li> <li>Matte White</li> </ul>	<ul style="list-style-type: none"> <li>Ruby Red RAL #3003</li> <li>Bright Orange RAL #2009</li> <li>Beige RAL #1001</li> <li>Traffic Yellow RAL #1023</li> <li>Island Skye RAL #6027</li> <li>Sky Blue RAL #5015</li> </ul>

\*Extended lead times for custom RAL finishes. Any RAL color can be selected in addition to the one shown

### Light Distribution



Standard Shapes			Custom Shapes				
L Configuration	Rectangle/Square Configuration	U Configuration	X Configuration	T Configuration	Hexagon Configuration	Triangle Configuration	Linear Abstract Configuration

\*More custom shapes are available upon request

Master Product Code Builder	
Prefix	LVLB
Profile	P24
Finish	
Satin Aluminum	leave blank
Matte Black	BLK
Matte White	WTH
Custom	C
Output	
70%/30%	70UP/30D, 70D, 30U
50%/50%	50U/50D
Size	
2ft	24
4ft	46
6ft	68
8ft	90
Custom	enter in inches
Continuous	CR
Custom Shape	CS
Color	
3000K	WW
4000K	NW
5000K	BW
Custom	enter CCT value
RGB+6000K	N/A
RGB+2700K	N/A
Tunable White	N/A
CRI	
80+	leave blank
90+	90
95+	95
Mount Type	
Mount to JBOX	A
Remote JBOX	B
Drop Ceiling	C
High Bay	D
Voltage	
120-277VAC	leave blank
347VAC	347
Dimming/Control	
0-10V	leave blank
Phase/TRIAC	TRIAC
DMX	DMX
Emergency	
None	leave blank
EM Back Up	EM* 4ft min for EM
Run Type	
Single	leave blank
C/R Powered End	CRP
C/R Middle	CRM
C/R End Piece	CRE
NA	leave blank
Shapes	
NA	leave blank
Standard Shape	S/S
Custom Shape	C/S

