

Linear LED Fixture Spec Sheet




LVLBP33-XX-YY-ZZ
Pendant and Surface Mounted Linear Lighting

Quick Specs

Part #	LVLBP33-XX-YY-ZZ
Sizes	2ft, 4ft, 6ft, 8ft
Input Voltage	120-277VAC
Light Output	SO: 687 lumens /ft HO: 1,243 lumens/ft
Efficiency	87 lumens/Watt
Color Rendering	>80 (CRI over 90 available)
Environment	Dry or Damp Location
Warranty	5-Year
Lifetime	50,000-70,000+ Hours
Listings	UL-Listed
Dimming	0-10V Dimmable to 1%

Dimensions



Available Color Temperatures

3000K



Warm White

4000K



Natural White

5000K



Bright White



Our 3" x 3" Linear LED Fixture is a high output linear light source suitable for general lighting applications. It can be both **surface mounted**, or **pendant (suspended) mounted** with cables for a wide variety of residential, commercial, retail, and hospitality lighting applications.

This linear LED fixture is available in **2ft**, **4ft**, **6ft**, and **8ft** sizes as one single piece. Select "**linkable**" option for seam-less continuous runs over 16ft. Choose from (2) light output levels: **SO** Standard Output (687 lumens/ft), or **HO** High-Output (1,243 lumens/ft).

Conveniently select from (3) standard color temperatures best suited to your space: **3000K** (Warm White), **4000K** (Natural White), **5000K** (Bright White).

Integral driver technology allows these fixtures to accept **universal 120-277VAC** input voltage, and are **fully dimmable to 1%** via 0-10V dimming wires.

Surface Mount View



GlowbackLED® | Bluegate Inc.

1173 NW 159th Drive Miami Gardens, FL
Miami Gardens, FL 33169
1-800-679-4902 • info@bluegateinc.com

GlowbackLED® is a registered trademark of Bluegate Inc.

©2021 Bluegate Inc. All Rights Reserved

Specifications subject to change without notice



Linear LED Fixture Spec Sheet



LVLBP33-XX-YY-ZZ
Pendant and Surface Mounted Linear Lighting

Surface Mounting

A Clip Mounting

B Direct-Screw Mounting

Pendant Mounting

Select Ceiling Type:

C Drywall/Solid mount to JBOX

B Drywall/Solid to remote JBOX

E Drop Ceiling mount to T-Bar

F High Bay mount to Structure

Run Type

Single Run:

2ft 4ft 6ft 8ft

Continuous Run:
Enter Length: _____

Powered End Center End

Detailed Product Specs

Fixture Size	Part #	Net Size	Wattage	Lumen Output
2ft	LVLBP33-SO-24-XX	24"	16	1,374
4ft	LVLBP33-SO-46-XX	46"	31	2,748
6ft	LVLBP33-SO-68-XX	68"	47	4,122
8ft	LVLBP33-SO-90-XX	90"	62	5,496
2ft	LVLBP33-HO-24-XX	24"	28	2,486
4ft	LVLBP33-HO-46-XX	46"	55	4,972
6ft	LVLBP33-HO-68-XX	68"	83	7,458
8ft	LVLBP33-HO-90-XX	90"	110	9,944

XX= Color Temp Code (WW=Warm White 3000K, NW=Natural White 4000K, BW= Bright White 5000K)

